

Automatic Emergency
3600 RPM NG/LP

Standby Power Ratings

60HZ	kVA 11	kW 11
-------------	---------------	--------------



Made in USA

Baldor Generator Features

- Baldor Generators are manufactured in an ISO9001 facility located in Oshkosh, Wisconsin
- Every generator is design, prototype, and production tested
- Brushless synchronous two-pole alternator
- Advanced noise technology - heavy gauge steel enclosure with superior sound insulation
- Durable powder coat paint finish
- Battery charger - 12V semi-float

Generator Ratings

Voltage	Phase	kW	PF	AMPS	Hz	Voltage Regulation	Frequency Regulation
120/240	1	11	1	45.8	60	+/-1%	+/-5%
*208/240/480	3	11	1	30.5/26.5/13.2	60	+/-1%	+/-5%

Options

- Automatic transfer switch
- *Stocked as single phase only. 3 phase available. Contact your Baldor district office.

Alternator Specifications

Manufacturer Baldor
Type 2-pole, revolving field
Leads 4
Voltage Regulator AVR
Voltage Regulation 1%
Insulation Material Class F
Temperature Rise 150° C
Bearing: quantity, type 1, sealed
Coupling type Flexible disc
One step load acceptance 100% of rating

Warranty:

- Limited 3 year warranty.
- 1 year or 1000 hours parts and labor.
- 3 years or 1000 hours parts.

Engine Specifications

Manufacturer Kohler
Model CH23GS
Horsepower 23 HP
Cylinders 2
Cycle 4-stroke
Induction system Naturally aspirated
Displacement, cc (cu. in.) 725 (44 cu. in.)
Bore and stroke 83mm x 67mm 3.27" x 2.64"
Lubrication capacity (with filter) 1.9 liters (2.0 qt.)
Cooling Air
Battery recommendation min. (cold cranking amps) 300
- Battery rack and cable supplied (battery not included)

Fuel Consumption

L-P Gas - Full Load 72 C.F.H.
Natural Gas - Full Load 200 C.F.H.

Ratings: - **Standby Ratings:** Standby ratings are applicable for supplying emergency power for the duration of a utility power outage. Primary power to the installation is utility supplied. No overload capability for standby rating. Standby ratings in accordance with ISO 3046, BS55114, DIN 6271. For additional information, please consult factory. **Single Phase:** Single phase units are rated at 1.0 (Unity) power factor. Manufacturer reserves the right to implement specifications or design changes without notice. Derate 10% for natural gas. **WARNING:** Do not connect generator to any building's electrical system unless a disconnect switch has been installed.

Distributed by:

Alternator Features

- Brushless design
- Class F insulation used throughout
- Solid state voltage regulation
- All wound components impregnated with varnish
- Sealed bearing
- Double coated copper wire
- Stamped steel winding locks for overspeed protection

Control Features

- Low oil pressure, overcrank shutdown protection, underspeed, high engine temp and fail to start with indicator lights
- Circuit breaker protection - Single phase only
- Remote start - stop connection

Engine Features

- Spin-on oil filter
- 12V flywheel alternator
- 12V starter motor
- Natural gas or LP operation

Warranty: 1 year limited per manufacturer.

Weight

Net 468 lbs.
Shipping 518 lbs.

Dimensions

46" X 30 3/8" X 30 1/2"

BALDOR
GENERATORS

3815 Oregon Street • Oshkosh, WI 54902
1-800-872-7697 • (920) 236-4200 • Fax (920) 236-4219

World Headquarters

Baldor Electric Company • P.O. Box 2400 • Fort Smith, AR 72902-2400 U.S.A.
Phone (479) 646-4711 • Fax (479) 648-5792 • International Fax (479) 648-5895

www.baldor.com

